



General ordering data

| | |
|------------------|--|
| Order No. | 1885240000 |
| Part designation | LSF-SMT3.50/8/135 1.5 |
| Version | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 8, 135°, Tube |
| EAN | 4032248490127 |
| Qty. | 19 pc(s). |

System parameters

| | |
|---------------------------------|--------------------------|
| Product family | System LS |
| Conductor connection system | Push In |
| Fitted to PCB | Reflow solder connection |
| Outgoing direction of conductor | 135° |
| Pitch | 3.5 mm |
| Pitch in inch | 0.138 inch |
| No. of poles | 8 |
| Fitted by customer | no |
| No. of rows | 1 |
| Solder pin length | 1.5 mm |
| Dia. of fitting hole | 1.1 mm |
| Fitting hole tolerance | + 0.1 mm |
| No. of solder pins per pole | 2 |
| Stripping length | 8 mm |

System parameters

| | |
|---|------------------------|
| L1 in mm | 24.5 mm |
| L1 in inch | 0.965 inch |
| Electric shock protection to DIN VDE 0470 | IP 20 |
| Electric shock protection to DIN VDE 0470 | Safe from finger touch |

Material data

| | |
|---------------------------|---------------------|
| Insulating material | LCP GF |
| Colour | black |
| colour chart | Similar to RAL 9011 |
| Insulating material group | IIIa |
| Flammability class UL 94 | V-0 |
| CTI | >= 175 |
| Contact base material | Copper alloy |
| Contact surface | tinned |
| Storage temperature, min. | -25 °C |
| Storage temperature, max. | 55 °C |

Connectable conductors

| | |
|---|----------------------|
| Clamping range, min. | 0.13 mm ² |
| Clamping range, max. | 1.5 mm ² |
| AWG, min. | 24 |
| AWG, max. | 16 |
| O.D. of conductor insulation, max. | 2.9 mm |
| Solid, min. H05(07) V-U | 0.2 mm ² |
| Solid, max. H05(07) V-U | 1.5 mm ² |
| Flexible, min. H05(07) V-K | 0.2 mm ² |
| Flexible, max. H05(07) V-K | 1.5 mm ² |
| With wire end ferrule, acc. to DIN 46 228/1, min. | 0.25 mm ² |
| With wire end ferrule, acc. to DIN 46 228/1, max. | 1.5 mm ² |
| w. plastic collar ferrule, DIN 46228 pt 4, min. | 0.25 mm ² |
| w. plastic collar ferrule, DIN 46228 pt 4, max. | 0.75 mm ² |

DIN IEC rating data

| | |
|--|------------------|
| Rated current, min. No. pins (Tu=20°C) | 17.5 A |
| Rated current, max. No. pins (Tu=20°C) | 16 A |
| Rated current, min. No. pins (Tu=40°C) | 17.5 A |
| Rated current, max. No. pins (Tu=40°C) | 14 A |
| Rated voltage for overvoltage class/pollution severity II/2 | 320 V |
| Rated voltage for overvoltage class/pollution severity III/2 | 160 V |
| Rated voltage for overvoltage class/pollution severity III/3 | 160 V |
| Rated impulse withstand voltage for overvoltage class/pollution severity II/2 | 2.5 kV |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/2 | 2.5 kV |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/3 | 2.5 kV |
| Short-time withstand current resistance | 3 x 1s with 80 A |

CSA rating data

| | |
|------------------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |
| AWG conductor (field wiring), min. | 24 |
| AWG conductor (field wiring), max. | 16 |

UL 1059 rating data

| | |
|-----------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |
| AWG conductor, min. | 24 |
| AWG conductor, max. | 16 |

Approvals

Approvals institutes



Classifications

| | |
|------------|-------------|
| eClass 5.1 | 27-26-11-01 |
|------------|-------------|

Similar products

| Order No. | Part designation | Version |
|------------|-----------------------|--|
| 1885650000 | LSF-SMT3.50/2/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 2, 135°, Tube |
| 1887340000 | LSF-SMT3.5/2/135 3.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 2, 135°, Tape |
| 1885180000 | LSF-SMT3.50/2/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 2, 135°, Tube |
| 1887550000 | LSF-SMT3.5/2/135 1.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 2, 135°, Tape |
| 1885660000 | LSF-SMT3.50/3/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 3, 135°, Tube |
| 1887350000 | LSF-SMT3.5/3/135 3.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 3, 135°, Tape |
| 1885190000 | LSF-SMT3.50/3/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 3, 135°, Tube |
| 1887560000 | LSF-SMT3.5/3/135 1.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 3, 135°, Tape |
| 1885670000 | LSF-SMT3.50/4/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 4, 135°, Tube |
| 1887360000 | LSF-SMT3.5/4/135 3.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 4, 135°, Tape |
| 1885200000 | LSF-SMT3.50/4/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 4, 135°, Tube |
| 1887580000 | LSF-SMT3.5/4/135 1.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 4, 135°, Tape |

| | | |
|------------|------------------------|---|
| 1885680000 | LSF-SMT3.50/5/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 5, 135°, Tube |
| 1887460000 | LSF-SMT3.5/5/135 3.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 5, 135°, Tape |
| 1885210000 | LSF-SMT3.50/5/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 5, 135°, Tube |
| 1887630000 | LSF-SMT3.5/5/135 1.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 5, 135°, Tape |
| 1885690000 | LSF-SMT3.50/6/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 6, 135°, Tube |
| 1887470000 | LSF-SMT3.5/6/135 3.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 6, 135°, Tape |
| 1885220000 | LSF-SMT3.50/6/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 6, 135°, Tube |
| 1887640000 | LSF-SMT3.5/6/135 1.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 6, 135°, Tape |
| 1885700000 | LSF-SMT3.50/7/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 7, 135°, Tube |
| 1887480000 | LSF-SMT3.5/7/135 3.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 7, 135°, Tape |
| 1885230000 | LSF-SMT3.50/7/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 7, 135°, Tube |
| 1887650000 | LSF-SMT3.5/7/135 1.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 7, 135°, Tape |
| 1885710000 | LSF-SMT3.50/8/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 8, 135°, Tube |
| 1887490000 | LSF-SMT3.5/8/135 3.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 8, 135°, Tape |
| 1887660000 | LSF-SMT3.5/8/135 1.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 8, 135°, Tape |
| 1885720000 | LSF-SMT3.50/9/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 9, 135°, Tube |
| 1887500000 | LSF-SMT3.5/9/135 3.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 9, 135°, Tape |
| 1885250000 | LSF-SMT3.50/9/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 9, 135°, Tube |
| 1887670000 | LSF-SMT3.5/9/135 1.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 9, 135°, Tape |
| 1885730000 | LSF-SMT3.50/10/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 10, 135°, Tube |
| 1887510000 | LSF-SMT3.5/10/135 3.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 10, 135°, Tape |
| 1885260000 | LSF-SMT3.50/10/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 10, 135°, Tube |
| 1887680000 | LSF-SMT3.5/10/135 1.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 10, 135°, Tape |
| 1885740000 | LSF-SMT3.50/11/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 11, 135°, Tube |
| 1887520000 | LSF-SMT3.5/11/135 3.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 11, 135°, Tape |
| 1885270000 | LSF-SMT3.50/11/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 11, 135°, Tube |

| | | |
|------------|------------------------|---|
| 1887690000 | LSF-SMT3.5/11/135 1.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 11, 135°, Tape |
| 1885750000 | LSF-SMT3.5/12/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 12, 135°, Tube |
| 1887530000 | LSF-SMT3.5/12/135 3.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 12, 135°, Tape |
| 1885280000 | LSF-SMT3.5/12/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 12, 135°, Tube |
| 1887700000 | LSF-SMT3.5/12/135 1.5R | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 12, 135°, Tape |
| 1885760000 | LSF-SMT3.5/13/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 13, 135°, Tube |
| 1885290000 | LSF-SMT3.5/13/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 13, 135°, Tube |
| 1885770000 | LSF-SMT3.5/14/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 14, 135°, Tube |
| 1885300000 | LSF-SMT3.5/14/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 14, 135°, Tube |
| 1885780000 | LSF-SMT3.5/15/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 15, 135°, Tube |
| 1885310000 | LSF-SMT3.5/15/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 15, 135°, Tube |
| 1885790000 | LSF-SMT3.5/16/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 16, 135°, Tube |
| 1885320000 | LSF-SMT3.5/16/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 16, 135°, Tube |
| 1885800000 | LSF-SMT3.5/17/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 17, 135°, Tube |
| 1885330000 | LSF-SMT3.5/17/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 17, 135°, Tube |
| 1885810000 | LSF-SMT3.5/18/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 18, 135°, Tube |
| 1885340000 | LSF-SMT3.5/18/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 18, 135°, Tube |
| 1885820000 | LSF-SMT3.5/19/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 19, 135°, Tube |
| 1885350000 | LSF-SMT3.5/19/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 19, 135°, Tube |
| 1885830000 | LSF-SMT3.5/20/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 20, 135°, Tube |
| 1885360000 | LSF-SMT3.5/20/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 20, 135°, Tube |
| 1885840000 | LSF-SMT3.5/21/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 21, 135°, Tube |
| 1885370000 | LSF-SMT3.5/21/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 21, 135°, Tube |
| 1885850000 | LSF-SMT3.5/22/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 22, 135°, Tube |
| 1885380000 | LSF-SMT3.5/22/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 22, 135°, Tube |
| 1885860000 | LSF-SMT3.5/23/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 23, 135°, Tube |

| | | |
|------------|------------------------|---|
| 1885390000 | LSF-SMT3.50/23/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 23, 135°, Tube |
| 1885870000 | LSF-SMT3.50/24/135 3.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 24, 135°, Tube |
| 1885400000 | LSF-SMT3.50/24/135 1.5 | PCB terminal, Push In, Reflow solder connection, Clamping range, max.: 1.5 mm ² , Pitch: 3.50 mm, No. of poles: 24, 135°, Tube |